## SAME FRUTTETO 3 FRUTTETO 3 60 CLASSIC (2010 AND AFTER)



<b>ENGINE</b> 1000.3-WTI Euro 3 Capacity: 8 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40
Check every 10 hours, change every 300 hours/ 12 months		
USE		CLIMATE
Biodiesel B100		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

DIFFERENTIAL FRONT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
	·	· · · · · · · · · · · · · · · · · · ·

Check every 300 hours, change every 1200 hours/ 12 months

Check every 10 hours, change every 150 hours

HUB REDUCTIONS FRONT Capacity: 1,5 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 300 hours, change ev	rery 1200 hours/ 12 months	,

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 41 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 50 hours, change every 1200 hours/ 12 months		

## SAME FRUTTETO 3 FRUTTETO 3 60 CLASSIC (2010 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Charles a variety 50 having a charge a variety 24 months		

Check every 50 hours, change every 24 months

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

COOLING SYSTEM Capacity: 12 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1	Noderale
Coolant SP 12 EVO	

Check every 10 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.