PRODUCT RECOMMENDATION

SAME IRON COM3 IRON 185 DCR (2008 AND AFTER)

ENGINE Deutz TCD 2012 L06 4V DCR
Capacity: 16,5 liter, Filter capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP 10W-40	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Biodiesel B100		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Agrisynth LSP 10W-40	**Agridiesel MSP 15W-40**	**Agridiesel CRD+ 15W-40**

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 10 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 1 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 10 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 10 liter (each hub)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 10 hours, change every 1000 hours/ 12 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

SAME IRON COM3 IRON 185 DCR (2008 AND AFTER)

POWER TAKE OFF FRONT
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	**Agrifluid HT**	

Check every 10 hours, change every 500 hours/ 12 months

TRANSAXLE/TRANSMISSION
Capacity: 78 liter (Rigid rear axle), Capacity: 80 liter (Suspended rear axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	**Agrifluid HT**	

Check every 10 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

COOLING SYSTEM
Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367