

SAME IRON COM3 IRON 200 (2006 AND AFTER)



ENGINE Deutz Euro 2
Capacity: 24 liter, Filter capacity: 1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE
First change only

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 13 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

Check every 10 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 2,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

Check every 10 hours, change every 1200 hours/ 12 months

POWER TAKE OFF FRONT
Capacity: 1,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

Check every 10 hours, change every 1200 hours/ 12 months

SAME IRON COM3 IRON 200 (2006 AND AFTER)



TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING

Capacity: 120 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Check every 10 hours, change every 1200 hours/ 12 months

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2400 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.