SAME LASER LASER 90 TURBO (1985-1990)



ENGINE Same 1054PT Capacity: 10,2 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every 150	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 150	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 150	hours	
USE		CLIMATE
use Normal		CLIMATE Cold
Normal PRODUCT RECOMMENDATION 1		
Normal		
Normal PRODUCT RECOMMENDATION 1	hours	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20	hours	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20	hours	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4)	hours	
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter	hours	Cold
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter USE	hours	CLIMATE
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter USE Normal	hours	CLIMATE
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter USE Normal PRODUCT RECOMMENDATION 1		CLIMATE
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter USE Normal PRODUCT RECOMMENDATION 1 Agrifluid HT		CLIMATE
Normal PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Check every 10 hours, change every 150 DIFFERENTIAL FRONT (4x4) Capacity: 13 liter USE Normal PRODUCT RECOMMENDATION 1 Agrifluid HT		CLIMATE

Normal

Agrifluid HT

PRODUCT RECOMMENDATION 1

Check every 150 hours, change every 1200 hours

Moderate

SAME LASER LASER 90 TURBO (1985-1990)



TRANSAXLE/TRANSMISSION Capacity: 76 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 150 hours, change every 2400 hours

HYDRAULIC SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 150 hours, change every 24	100 hours	

HYDRAULIC BRAKE SYSTEM

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

ATF Dexron II-D ATF-A

POWER STEERING Capacity: 2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
ATF Dexron II-D	ATF-A		
Chack avery 150 hours, change ave	ory 1200 hours		

Check every 150 hours, change every 1200 hours

GREASE POINTS/NIPPLES OTHE	RS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		

SAME LASER LASER 90 TURBO (1985-1990)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Chack avery 50 hours, change ave	ny 1200 hours	-

Check every 50 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.