

SAMPO ROSENLEW COMIA COMIA C4 (2012 AND AFTER)



ENGINE Sisu
Capacity: 13 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 3
Dieselfleet LSP Ultra 10W-30

Check every 10 hours, change every 300 hours/ 12 months

FINAL DRIVES CIT
Capacity: 3 liter (each side)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 1200 hours/ 24 months

FINAL DRIVES Dana
Capacity: 6 liter (Left), Capacity: 5,5 liter (Right)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 1200 hours/ 24 months

GEARBOX HYDROSTATIC
Capacity: 3,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

GEARBOX MECHANICAL
Capacity: 3 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

SAMPO ROSENLEW COMIA COMIA C4 (2012 AND AFTER)



GRAIN ELEVATOR GEARBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 00/000		

KNIFE DRIVE GEARBOX

Capacity: 0,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

RETURN AUGER GEARBOX

Capacity: 0,35 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

HYDRAULIC SYSTEM

Capacity: 22 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 600 hours/ 12 months

GREASE POINTS/NIPPLES GREASE LUBRICATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

SAMPO ROSENLEW COMIA COMIA C4

(2012 AND AFTER)



GREASE POINTS/NIPPLES OIL LUBRICATED

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

COOLING SYSTEM

Capacity: 29 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.