

SCHLÜTER COMPACT COMPACT 1050 T, COMPACT 1050 TV (1982 AND AFTER)



ENGINE SDM 110 W4
Capacity: 10 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Change every 150 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

Change every 150 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40

Change every 150 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 150 hours, change every 1050 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 150 hours, change every 1050 hours/ 12 months

SCHLÜTER COMPACT COMPACT 1050 T, COMPACT 1050 TV (1982 AND AFTER)



HUB REDUCTIONS REAR

Capacity: 5,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 150 hours, change every 1050 hours/ 12 months*

TRANSMISSION/HYDRAULIC SYSTEM 12/6

Capacity: 36 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

PRODUCT RECOMMENDATION 2

Multifleet SCD 20W-20*Change every 1050 hours/ 12 months*

HYDRAULIC CAB TILT SYSTEM

Capacity: 1,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 20W-20

FLUID CLUTCH

Capacity: 9,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 5000 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 150 hours, change every 12 months*

SCHLÜTER COMPACT COMPACT 1050 T, COMPACT 1050 TV (1982 AND AFTER)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Check every 150 hours, change every 12 months

POWER STEERING

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 150 hours, change every 1050 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 50 hours

COOLING SYSTEM

Capacity: 14,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.