SHIBAURA CM SERIES CM304 (2000 AND AFTER)



ENGINE J843 Capacity: 4,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	Multifleet SCD 30
Check every 10 hours, change every 100) hours	·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SCD 10W
Check every 10 hours, change every 100) hours	·
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		

DIFFERENTIAL REAR Capacity: 1,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 50 hours, change every 600 hours

Check every 10 hours, change every 100 hours

Multifleet SCD 20W-20

TRANSMISSION/HYDRAULIC SYSTEM FRONT Capacity: 17 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Perlus H 46	Perlus AF 46			
Check every 50 hours, change ever	y 600 hours	·		

SHIBAURA CM SERIES CM304 (2000 AND AFTER)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours		

COOLING SYSTEM Capacity: 6,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change even	v 12 months		

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.