

SHIBAURA ST ST318 (HST) (1998 AND AFTER)



ENGINE S753
Capacity: 3 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 20W-50

PRODUCT RECOMMENDATION 3
Multifleet SCD 30

Check every 10 hours, change every 100 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Multifleet SCD 10W

Check every 10 hours, change every 100 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Check every 10 hours, change every 100 hours

DIFFERENTIAL FRONT
Capacity: 1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
SP Gear 5015

PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W

Check every 50 hours, change every 300 hours

HUB REDUCTIONS FRONT
Capacity: 0,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
SP Gear 5015

PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W

Check every 50 hours, change every 300 hours

SHIBAURA ST ST318 (HST) (1998 AND AFTER)



TRANSAXLE HYDROSTATIC/HYDRAULIC SYSTEM

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

Check every 50 hours, change every 300 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.