

STEYR 8300 8300, 8300A (1988-1994)

ENGINE WD 615.84
Capacity: 19 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	Multifleet SCD 40

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SCD 20W-20

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 6,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

DIFFERENTIAL REAR (4x4)
Capacity: 4,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 500 hours, change every 1000 hours

STEYR 8300 8300, 8300A (1988-1994)**HUB REDUCTIONS FRONT (4x4)**

Capacity: 4,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours***HUB REDUCTIONS REAR**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours/ 12 months***POWER TAKE OFF**

Capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 500 hours, change every 1000 hours***TRANSMISSION HYDROSTATIC/HYDRAULIC SYSTEM**

Capacity: 58 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30***Check every 500 hours, change every 1000 hours/ 12 months***POWER STEERING**

Capacity: 2,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 250 hours*

STEYR 8300 8300, 8300A (1988-1994)**GREASE POINTS/NIPPLES OTHERS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

Check every 500 hours

COOLING SYSTEM

Capacity: 51 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.