

STEYR 900 955, 955A [CHASSISNO. 1739 ->] (1996 AND AFTER)



ENGINE WD 301.42/43
Capacity: 6,6 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SCD 40	HDX 40

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	HDX 20W-20

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

DIFFERENTIAL FRONT LIMITED SLIP (4x4)
Capacity: 4,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

STEYR 900 955, 955A [CHASSISNO. 1739 ->] (1996 AND AFTER)



HUB REDUCTIONS FRONT (4x4)

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

TRANSAXLE MANUAL 16/8

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HYDRAULIC SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Change every 2000 hours/ 24 months

POWER STEERING

Capacity: 2,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 250 hours, change every 2000 hours/ 24 months

STEYR 900 955, 955A [CHASSISNO. 1739 ->] (1996 AND AFTER)



GREASE POINTS/NIPPLES OTHERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Check every 50 hours</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	
<i>Check every 50 hours</i>		

COOLING SYSTEM

Capacity: 13,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Check every 10 hours, change every 1000 hours/ 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.