

**STEYR 9000 MT 9095 MT (2008 AND AFTER)****ENGINE**

Capacity: 12 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel MSP 15W-40****PRODUCT RECOMMENDATION 2****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 10W-40***Check every 10 hours, change every 500 hours/ 12 months***DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 4,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90****HUB REDUCTIONS FRONT (4X4) + BRAKES**

Capacity: 1,7 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90****HUB REDUCTIONS FRONT (4X4) WITHOUT BRAKES**

Capacity: 0,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90****PRODUCT RECOMMENDATION 3****Gearlube GL-5 85W-140**

**STEYR 9000 MT 9095 MT (2008 AND AFTER)****POWER TAKE OFF FRONT**

Capacity: 1 liter

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Moderate                     |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Alternative (acceptable)    |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak MTH 10W-30</b> |  |          |

**TRANSAXLE MANUAL 16/8**

Capacity: 38 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak MTH 10W-30</b> |  |          |

**HYDRAULIC SYSTEM POWER STEERING**

Capacity: 34 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Perlus H 46</b>       | <b>Perlus AF 46</b>      |          |

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>LHM +</b>             |  |          |

**GREASE POINTS/NIPPLES**

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

**STEYR 9000 MT 9095 MT (2008 AND AFTER)****COOLING SYSTEM**

Capacity: 12 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     |          |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*