

STEYR 9000 9086, 9086A TURBO (1992-1997)

ENGINE WD 401.81
Capacity: 8,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	Multifleet SCD 40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SCD 20W-20

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT LIMITED SLIP (4x4)
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

STEYR 9000 9086, 9086A TURBO (1992-1997)**TRANSAXLE MANUAL 32/32**

Capacity: 32 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 12 months/ 500 hours, change every 1000 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 34 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 46****PRODUCT RECOMMENDATION 2****Perlus H 68****PRODUCT RECOMMENDATION 3****Perlus AF 46***Check every 12 months/ 500 hours, change every 1000 hours/ 24 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**LHM +***Check every 12 months/ 500 hours, change every 1000 hours/ 24 months***POWER STEERING**

Capacity: 2,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 250 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES OTHERS****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 50 hours*

STEYR 9000 9086, 9086A TURBO (1992-1997)**GREASE POINTS/NIPPLES WHEEL BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	

Check every 50 hours

COOLING SYSTEM

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.