

STEYR 9100 9170A TURBO (1994 AND AFTER)

**ENGINE**

Capacity: 21 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Multifleet SHPD 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 20W-50****PRODUCT RECOMMENDATION 3****Multifleet SCD 40***Check every 10 hours, change every 250 hours/ 12 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40****PRODUCT RECOMMENDATION 3****Multifleet SCD 20W-20***Check every 10 hours, change every 250 hours/ 12 months***USE**

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1**Multifleet SCD 10W***Check every 10 hours, change every 250 hours/ 12 months***DIFFERENTIAL FRONT**

Capacity: 11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 12 months/ 500 hours, change every 1000 hours/ 24 months***HUB REDUCTIONS FRONT**

Capacity: 1,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

STEYR 9100 9170A TURBO (1994 AND AFTER)



HUB REDUCTIONS REAR

Capacity: 3,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING

Capacity: 75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Agrifluid HT*Check every 12 months/ 500 hours, change every 1000 hours/ 24 months*

GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

COOLING SYSTEM

Capacity: 27 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours, change every 1000 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.