

STEYR MULTITRAC/KOMMUNAL 900 MULTITRAC M952 (1998 OG EFTER)



MOTOR Perkins 903
Kapacitet: 7,5 liter

ANVEND	KLIMA
Normal	Middelhavssagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Multifleet SHPD 15W-40	Multifleet SCD 40	HDX 40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	HDX 20W-20

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1		
HDX 10W		

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

KRAFTOVERFØRING FOR
Kapacitet: 1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 10 timer, skift alle 100 timer/ 12 måneder

TRANSAKSEL MANUEL
Kapacitet: 22 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

STEYR MULTITRAC/KOMMUNAL 900 MULTITRAC M952 (1998 OG EFTER)



HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 9,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

PRODUKTANBEFALING 2

Perlus H 46

PRODUKTANBEFALING 3

Perlus AF 46

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

LHM +

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 12 liter, Kapacitet: 13 liter (+ varmeapparat)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.