

# STEYR MULTITRAC/KOMMUNAL 900 MULTITRAC M963 (1998 OG EFTER)



**MOTOR** Perkins 903.T  
Kapacitet: 7,5 liter

|        |                 |
|--------|-----------------|
| ANVEND | KLIMA           |
| Normal | Middelhavsgtigt |

|                               |                          |                     |
|-------------------------------|--------------------------|---------------------|
| PRODUKTANBEFALING 1           | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3 |
| <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 40</b> | <b>HDX 40</b>       |

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                             |                               |                     |
|-----------------------------|-------------------------------|---------------------|
| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3 |
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> | <b>HDX 20W-20</b>   |

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Arktisk |

|                     |  |  |
|---------------------|--|--|
| PRODUKTANBEFALING 1 |  |  |
| <b>HDX 10W</b>      |  |  |

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

**KRAFTOVERFØRING FOR**  
Kapacitet: 1 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                          |                             |                     |
|--------------------------|-----------------------------|---------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 10 timer, skift alle 100 timer/ 12 måneder

**TRANSAKSEL MANUEL**  
Kapacitet: 22 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                          |                             |                     |
|--------------------------|-----------------------------|---------------------|
| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2         | PRODUKTANBEFALING 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b> |

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

# STEYR MULTITRAC/KOMMUNAL 900

## MULTITRAC M963 (1998 OG EFTER)



### HYDRAULIKSYSTEM SERVOSTYRING

Kapacitet: 9,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF Dexron II-D**

PRODUKTANBEFALING 2

**Perlus H 46**

PRODUKTANBEFALING 3

**Perlus AF 46**

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

### HYDRAULISK BREMSESYSTEM

Kapacitet: 0,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**LHM +**

Kontroller alle 250 timer, skift alle 2000 timer/ 24 måneder

### SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

Kontroller alle 50 timer

### KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

Kontroller alle 250 timer, skift alle 1000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.