TORO GROUNDSMASTER GROUNDSMASTER 4010-D 30446, 312000001->



ENGINE Kubota V2403T Capacity: 9,5 liter		
use Normal		climate Moderate
Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 150 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours/ 12 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Change avery 200 hours	-	

Change every 200 hours

PLANETARY DRIVES Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 400 hours, change ever	rv 800 hours/ 12 months	

Change every 200 hours		
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
First change only		Moderate
USE		CLIMATE

PRODUCT RECOMMENDATION

TORO GROUNDSMASTER GROUNDSMASTER 4010-D 30446, 312000001->



HYDRAULIC SYSTEM Capacity: 30,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		
Check every 10 hours, change every 800	hours	

COOLING SYSTEM Capacity: 12,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		
Check every 10 hours, change ever	v 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.