

TORO GROUNDMASTER

GROUNDMASTER 4010-D 30603,

313000001->



ENGINE Yanmar
Capacity: 5,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL REAR
Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours/ 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 200 hours

PLANETARY DRIVES
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours/ 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 200 hours

TORO GROUNDMASTER

GROUNDMASTER 4010-D 30603,

313000001->

**HYDRAULIC SYSTEM**

Capacity: 29,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Check every 10 hours, change every 800 hours***COOLING SYSTEM**

Capacity: 8,52 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.