

# TORO UTILITY VEHICLES WORKMAN HDX-D 4X4 07371, 310000001->



**ENGINE** Kubota 902D  
Capacity: 3,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 150 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

*Check every 10 hours, change every 150 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Armado Synth 5W-30**

*Check every 10 hours, change every 150 hours*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40**

*Check every 10 hours, change every 50 hours*

USE	CLIMATE
First change only	Cold

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

PRODUCT RECOMMENDATION 2

**Armado Synth 5W-30**

*Check every 10 hours, change every 50 hours*

# TORO UTILITY VEHICLES WORKMAN HDX-D 4X4 07371, 310000001->



## DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

Check every 1 months/ 100 hours, change every 800 hours

## TRANSAXLE AUTOMATIC

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Matic 2032</b>	<b>ATF Almirol</b>	

Check every 10 hours, change every 800 hours

## HYDRAULIC SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 46</b>		

Check every 10 hours, change every 800 hours

## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 10 hours, change every 1000 hours/ 24 months

## COOLING SYSTEM

Capacity: 3,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.