

# TORPEDO ALL MODELS TX 55A (1986-1990)



**ENGINE** Deutz F3L-912  
Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 100 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 3,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

**TRANSAXLE MANUAL 8/2**  
Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Unigear HS GL-3/GL-5 80W-90**

*Check every 10 hours, change every 1000 hours/ 12 months*

**HYDRAULIC SYSTEM**  
Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Multifleet SCD 20W-20**

*Check every 10 hours, change every 1000 hours/ 12 months*

**TORPEDO ALL MODELS TX 55A (1986-1990)****GREASE POINTS/NIPPLES**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Multi Purpose Grease 3***Check every 100 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*