

TYM TRAKTORER T390 4WD KUBOTA V1903 (2005 OG EFTER)



MOTOR Kubota V1903
Kapacitet: 5,8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 100 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak MTH 10W-30

PRODUKTANBEFALING 2
Multifleet SHPD 10W-40

Skift alle 50 timer

DIFFERENTIALE FOR
Kapacitet: 8,8 liter (+ navreduktioner)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Unigear HS GL-3/GL-5 80W-90

Kontroller alle 100 timer, skift alle 600 timer

TRANSAKSEL MANUEL 12/12
Kapacitet: 34 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Agrifluid HT

Kontroller alle 10 timer, skift alle 300 timer

ANVEND
Første Service

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid HT-Plus

PRODUKTANBEFALING 2
Agrifluid HT

Skift alle 50 timer

TYM TRAKTORER T390 4WD KUBOTA V1903 (2005 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.