

TYM TRACTORS T433 2WD 404C-22 (2008 AND AFTER)

**ENGINE 404C-22 (C2.2)**

Capacity: 8,2 liter

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SHPD 20W-50 |

Check every 10 hours, change every 100 hours/ 12 months

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 10W-40 | | |

Check every 10 hours, change every 100 hours/ 12 months

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SHPD 20W-50 |

Change every 50 hours

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 10W-40 | | |

*Change every 50 hours***TRANSAXLE MANUAL 16/16**

Capacity: 35 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Check every 10 hours, change every 300 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrifluid HT-Plus | Agrifluid HT | |

Change every 50 hours

TYM TRACTORS T433 2WD 404C-22 (2008 AND AFTER)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 900 hours

COOLING SYSTEM

Capacity: 8,5 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.