

URSUS 12/14 SERIES 3512-CAB 2WD / 3514-CAB 4WD (1987 AND AFTER)



ENGINE 3250
Capacity: 6,8 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Multifleet SHPD 15W-40

Check every 10 hours, change every 200 hours

HUB REDUCTIONS FRONT
Capacity: 1,4 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
SP Gear 5015

PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W

Check every 100 hours, change every 800 hours

HUB REDUCTIONS REAR
Capacity: 1,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
SP Gear 5015

PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W

Check every 100 hours, change every 800 hours

TRANSAXLE MANUAL
Capacity: 40 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
SP Gear 5015

PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W

Check every 100 hours, change every 800 hours

HYDRAULIC SYSTEM POWER STEERING
Capacity: 1,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Perlus H 32

PRODUCT RECOMMENDATION 2
Perlus AF 32

Check every 100 hours, change every 800 hours

URSUS 12/14 SERIES 3512-CAB 2WD / 3514-CAB 4WD (1987 AND AFTER)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Check every 50 hours</i>		

COOLING SYSTEM

Capacity: 10,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
<i>Change every 24 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.