

# VALPADANA JUPITER JUPITER 40 (1540) EURO 1 (1999-2003)



**MOTOR** Yanmar 3TNE88-LAN  
Kapacitet: 4,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Skift alle 250 timer/ 12 måneder*

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 20W-20**

*Skift alle 250 timer/ 12 måneder*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Multifleet SHPD 15W-40**

PRODUKTANBEFALING 2

**Multifleet SCD 10W**

*Skift alle 250 timer/ 12 måneder*

**DIFFERENTIALE FOR (4x4)**  
Kapacitet: 3,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 2

**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 1000 timer/ 12 måneder*

**TRANSAKSEL/HYDRAULISK SYSTEM 12/12**  
Kapacitet: 24 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3

**Agrifluid HT**

*Skift alle 1000 timer/ 12 måneder*

# VALPADANA JUPITER JUPITER 40 (1540) EURO 1 (1999-2003)



## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 2

**MP Lithep Grease EP 2**

*Kontroller alle 500 timer*

## KØLESYSTEM

Kapacitet: 2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Skift alle 1000 timer/ 12 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*