

VALTRA (VALMET) 4000 METTA 4400 (METTA) (1994-1996)



ENGINE 320 DS
Capacity: 7 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 2

Multifleet SHPD 10W-40

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 500 hours, change every 1000 hours/ 12 months

TRANSAXLE MANUAL 12/8
Capacity: 23 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

Check every 500 hours, change every 1000 hours/ 12 months

VALTRA (VALMET) 4000 METTA 4400 (METTA) (1994-1996)



HYDRAULIC SYSTEM

Capacity: 32 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3

Perlus H 46*Check every 250 hours, change every 1000 hours/ 12 months*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 250 hours, change every 2000 hours/ 24 months*

GREASE POINTS/NIPPLES DRIVE SHAFT BEARING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 12 months/ 1000 hours*

GREASE POINTS/NIPPLES GEAR LEVER LOWER END JOINTS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 250 hours*

GREASE POINTS/NIPPLES OTHERS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

VALTRA (VALMET) 4000 METTA 4400 (METTA) (1994-1996)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12 months/ 1000 hours

COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.