

VALTRA (VALMET) C SERIES C110 (2004-2006)



ENGINE Sisu 44DTA
Capacity: 19 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 500 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

Check every 500 hours, change every 1000 hours/ 12 months

VALTRA (VALMET) C SERIES C110 (2004-2006)



POWER TAKE OFF FRONT

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Check every 500 hours, change every 1000 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 45 liter, Capacity: 65 liter ('extra max' capacity), Capacity: 55 liter ('max' capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 12 months/ 500 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.