VERSATILE HHT SERIES 575 (2006 AND AFTER)



ENGINE Cummins QSX15 Capacity: 44 liter, Filter capacity: 3,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 250 h	nours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Check every 10 hours, change every 250 hours		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Armado Synth 5W-30		
Check every 10 hours, change every 250 hours		
DIFFERENTIAL AFTER S/N 700495 Capacity: 37 liter (housing), Capacity: 57 liter (System)		

	1	1	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Mediterranean	
USE		CLIMATE	
Capacity: 37 liter (housing), Capacity: 57 liter (System)			

Check every 50 hours, change every 500 hours

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Arctic
USE		CLIMATE

Check every 50 hours, change every 500 hours

VERSATILE HHT SERIES 575 (2006 AND AFTER)



DIFFERENTIAL BEFORE S/N 700495 Capacity: 55 liter (housing), Capacity: 75 liter (System)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140			
Check every 50 hours, change every 500 h	nours			
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			

Check every 50 hours, change every 500 hours

HUB REDUCTIONS Capacity: 10 liter (each hub)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 50 hours, change every 500 hours

Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Normal		Arctic
USE		CLIMATE

Check every 50 hours, change every 500 hours

TRANSMISSION CAT TA22 Capacity: 64 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 10 hours, change every 1000 hours		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 250 hours

VERSATILE HHT SERIES 575 (2006 AND AFTER)



TRANSMISSION Twin Disc 1407 Capacity: 47,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT-Plus	

Check every 10 hours, change every 1200 hours

TRANSMISSION SYNCROMESH Capacity: 37,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 1500 hours

HYDRAULIC SYSTEM Capacity: 155,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 1500 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 15	
Chack avery 10 hours abando avery 200	·

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.