

YANMAR FE FE-240H (2000 OG EFTER)



MOTOR Yanmar 3TNE78A
Kapacitet: 3,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 100 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

Skift alle 50 timer

DIFFERENTIALE FOR
Kapacitet: 3,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	SP Gear 5015

Kontroller alle 50 timer, skift alle 300 timer

TRANSAKSEL/HYDRAULISK SYSTEM/SERVOSTYRING
Kapacitet: 18 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	SP Gear 5015

Kontroller alle 50 timer, skift alle 300 timer

KØLESYSTEM
Kapacitet: 3,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.