

# ZETOR 11 / 45 9211, 9245 4WD (1989 AND AFTER)

**ENGINE Z8002.1334**

Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Check every 10 hours, change every 200 hours*

USE	CLIMATE
First change only	Moderate

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40***Change every 50 hours***DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 3,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Check every 100 hours, change every 1200 hours***HUB REDUCTIONS FRONT (4x4)**

Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W***Check every 100 hours, change every 1200 hours***HUB REDUCTIONS REAR**

Capacity: 4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

## PRODUCT RECOMMENDATION 2

**SP Gear 5015**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W***Check every 100 hours, change every 1200 hours*

# ZETOR 11 / 45 9211, 9245 4WD (1989 AND AFTER)



## TRANSAXLE/HYDRAULIC SYSTEM 8/4

Capacity: 47 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid HT-Plus</b>	<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>

Check every 50 hours, change every 1200 hours

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

Check every 10 hours, change every 24 months

## POWER STEERING

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

Check every 10 hours, change every 1200 hours

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 50 hours

## COOLING SYSTEM

Capacity: 21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 10 hours, change every 24 months

PRODUCT RECOMMENDATION

# ZETOR 11 / 45 9211, 9245 4WD (1989 AND AFTER)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*