

ZETOR 11 / 45 12211, 12245 4WD (1989 OG EFTER)



MOTOR Z8701.12
Kapacitet: 19 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

Skift alle 50 timer

NAVREDUKTIONER BAG

Kapacitet: 4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 100 timer, skift alle 1200 timer

NAVREDUKTIONER FOR (4x4)

Kapacitet: 1,25 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Kontroller alle 100 timer, skift alle 1200 timer

SELVSPÆRRENDE DIFFERENTIALE FOR

Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Gearlube LS 80W-90

Kontroller alle 100 timer, skift alle 1200 timer

ZETOR 11 / 45 12211, 12245 4WD (1989 OG EFTER)



TRANSAKSEL/HYDRAULISK SYSTEM 8/4

Kapacitet: 49 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Kontroller alle 50 timer, skift alle 1200 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,75 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 10 timer, skift alle 24 måneder

SERVOSTYRING

Kapacitet: 8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 10 timer, skift alle 1200 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 27 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 12 måneder

ZETOR 11 / 45 12211, 12245 4WD (1989 OG EFTER)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.