

ZETOR FORTERRA FORTERRA HSX 100

ZETOR 1005 (ST.3A) (2012 OG EFTER)



MOTOR Zetor 1005
Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 10W-40

Skift alle 100 timer

DIFFERENTIALE FOR
Kapacitet: 6,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Gearlube LS 80W-90	

Kontroller alle 100 timer, skift alle 1000 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Gearlube LS 80W-90	

Skift alle 100 timer

KRAFTOVERFØRING FOR
Kapacitet: 2,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 2032	ATF Almirol	

Kontroller alle 100 timer, skift alle 500 timer

ZETOR FORTERRA FORTERRA HSX 100

ZETOR 1005 (ST.3A) (2012 OG EFTER)



NAVREDUKTIONER FOR

Kapacitet: 0,6 liter (hver (2x))

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Gearlube LS 80W-90	

Kontroller alle 100 timer, skift alle 1000 timer

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Gearlube LS 80W-90	

Skift alle 100 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 60 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Kroontrak MTH 10W-30		

Kontroller alle 100 timer, skift alle 1000 timer

HYDROSTATISK STYRESYSTEM

Kapacitet: 2,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Perlus H 32	Perlus AF 32	

Kontroller alle 10 timer, skift alle 1500 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid DOT 3		

Kontroller alle 10 timer, skift alle 24 måneder

ZETOR FORTERRA FORTERRA HSX 100

ZETOR 1005 (ST.3A) (2012 OG EFTER)



SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 2

MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 20,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.