

ALLISON TRANSMISSIONS 2000 SERIES

(2001-2009)



TRANSMISSION AUTOMATIC Allison
Capacity: 10 liter, Capacity: 7 liter (shallow sump)

USE	CLIMATE
Severe (preferred)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Change every 120000 km/ 36 months/ 3000 hours

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Change every 80000 km/ 24 months/ 2000 hours

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

Change every 240000 km/ 48 months/ 4000 hours

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Change every 20000 km/ 6 months/ 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.