

ALLISON TRANSMISSIONS MD 3000 SERIES (2001-2010)

**TRANSMISSION AUTOMATIC Allison**

Capacity: 30 liter, Capacity: 16 liter (with 2 inch sump), Capacity: 18 liter (with 4 inch sump)

USE	CLIMATE
Severe (preferred)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 120000 km/ 36 months/ 3000 hours*

USE	CLIMATE
Normal (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 40000 km/ 12 months/ 1000 hours*

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2

SP Matic 2032

PRODUCT RECOMMENDATION 3

ATF Almirol*Change every 40000 km/ 12 months/ 1000 hours*

USE	CLIMATE
Normal (preferred)	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 240000 km/ 48 months/ 4000 hours*

USE	CLIMATE
Severe (alternative)	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 20000 km/ 6 months/ 500 hours*

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

PRODUCT RECOMMENDATION 2

SP Matic 2032

PRODUCT RECOMMENDATION 3

ATF Almirol*Change every 20000 km/ 6 months/ 500 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.