## AVIA (DAEWOO) D-LINE D120 (117 KW) EURO 5 (2009 AND AFTER)



<b>ENGINE</b> Cummins ISBe 4 Capacity: 13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

DIFFERENTIAL REAR Albion 8.20 Capacity: 8 liter, Capacity: 0,25 liter (each hub)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140		

GEARBOX ZF S6-850 6/1 Capacity: 7,5 liter, Capacity: 8 liter (+ PTO)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90	

Change every 60000 km/ 18 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

## AVIA (DAEWOO) D-LINE D120 (117 KW) EURO 5 (2009 AND AFTER)



POWER STEERING Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

COOLING SYSTEM Capacity: 17,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.