

AVIA (DAEWOO) D-LINE D90 (152 KW)

EURO 5 (2009 AND AFTER)



ENGINE Cummins ISBe 4
Capacity: 13 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Armado Synth LSP 10W-40

PRODUCT RECOMMENDATION 3

Armado Synth 10W-40

DIFFERENTIAL REAR Albion 8.20
Capacity: 8 liter, Capacity: 0,25 liter (each hub)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

GEARBOX ZF S6-850 6/1
Capacity: 7,5 liter, Capacity: 8 liter (+ PTO)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W-90

Change every 60000 km/ 18 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,65 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

HYDRAULIC CLUTCH SYSTEM
Capacity: 0,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3

AVIA (DAEWOO) D-LINE D90 (152 KW)

EURO 5 (2009 AND AFTER)



POWER STEERING

Capacity: 1,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

COOLING SYSTEM

Capacity: 17,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.