

BMC PROFESSIONAL / PROFESYONEL

PRO 1142 4X2 EURO 2 (2006-2010)



ENGINE Cummins ISMe 410-20 (Euro 2)
Capacity: 37 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 50000 km/ 6 months/ 500 hours

USE	CLIMATE
Long distance, >120000 km/year	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 60000 km/ 6 months/ 700 hours

USE	CLIMATE
Heavy Duty	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 30000 km/ 6 months/ 400 hours

DIFFERENTIAL REAR Meritor MS-18
Capacity: 21 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 80000 km/ 12 months/ 1000 hours

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 40000 km/ 6 months/ 500 hours

BMC PROFESSIONAL / PROFESYONEL

PRO 1142 4X2 EURO 2 (2006-2010)


TRANSMISSION MANUAL ZF 16S-2220 TO 16/2

Capacity: 12-15 liter

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 80000 km/ 1000 hours

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 40000 km/ 500 hours

HYDRAULIC CAB TILT SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH SYSTEM		
Capacity: 0,3 liter		
USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 30000 km/ 6 months/ 500 hours, change every 90000 km/ 12 months/ 1000 hours

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 15000 km, change every 45000 km/ 6 months/ 500 hours

BMC PROFESSIONAL / PROFESYONEL

PRO 1142 4X2 EURO 2 (2006-2010)



POWER STEERING

Capacity: 2,9 liter

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 30000 km/ 6 months/ 500 hours, change every 90000 km/ 12 months/ 1000 hours

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 15000 km, change every 45000 km/ 6 months/ 500 hours

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

GREASE POINTS/NIPPLES GENERAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.