

BMC PROFESSIONAL / PROFESYONEL

PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



ENGINE Cummins C8.3 (Euro 1)
Capacity: 24 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 20000 km/ 3 months/ 250 hours

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 10000 km/ 3 months/ 250 hours

DIFFERENTIAL REAR Meritor MS-18
Capacity: 21 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 60000 km/ 12 months/ 1000 hours

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 40000 km/ 6 months/ 500 hours

TRANSMISSION MANUAL ZF 16S-109 DT 16/2
Capacity: 9 liter

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 60000 km/ 12 months/ 1000 hours

USE	CLIMATE
All other conditions	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90

Change every 40000 km/ 6 months/ 500 hours

BMC PROFESSIONAL / PROFESYONEL

PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



HYDRAULIC CAB TILT SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,3 liter

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 20000 km/ 3 months/ 250 hours, change every 60000 km/ 12 months/ 1000 hours

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10000 km/ 3 months/ 250 hours, change every 40000 km/ 6 months/ 500 hours

POWER STEERING

Capacity: 2,9 liter

USE		CLIMATE
Long distance		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 20000 km/ 3 months/ 250 hours, change every 60000 km/ 12 months/ 1000 hours

USE		CLIMATE
All other conditions		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km/ 3 months/ 250 hours, change every 40000 km/ 6 months/ 500 hours

CENTRAL LUBRICATION SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

BMC PROFESSIONAL / PROFESYONEL

PRO 827 4X2/6X2/8X2 EURO 1 (2006-2010)



GREASE POINTS/NIPPLES GENERAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 32,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.