

CUMMINS ISB / ISC / ISL (2010) EPA 10 ISB 6.7 EPA 10 (2010 AND AFTER)



ENGINE Cummins ISB

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet MSP 15W-40

Change every 15000 miles/ 6 months/ 500 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Armado Synth LSP Ultra 5W-30

PRODUCT RECOMMENDATION 2

Armado Synth MSP 5W-40

PRODUCT RECOMMENDATION 3

Dieselfleet LSP Ultra 10W-30

Change every 15000 miles/ 6 months/ 500 hours

COOLING SYSTEM Cummins

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant SP 12 EVO

Change every 150000 miles/ 400 hours

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.