

# DAF F2100, F2300, F2500 F2300 DHT (6X2) (1987-1990)



**ENGINE DHT 825**  
Capacity: 22 liter

| USE                        |                             | CLIMATE                       |
|----------------------------|-----------------------------|-------------------------------|
| Normal                     |                             | Moderate                      |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3      |
| <b>Armado Synth 10W-40</b> | <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> |

**DIFFERENTIAL REAR 2699**  
Capacity: 16 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      | <b>Gearlube GL-4 80W</b> |

*Change every 12 months*

**HUB REDUCTIONS REAR 2699**  
Capacity: 2 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      | <b>Gearlube GL-4 80W</b> |

*Change every 12 months*

**TRANSMISSION MANUAL ZF S6-65 6/1**  
Capacity: 11 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> | <b>HDX 40</b>            |

**TRANSMISSION MANUAL ZF S6-80 + GV 80 12/2**  
Capacity: 15 liter

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> | <b>HDX 40</b>            |

# DAF F2100, F2300, F2500 F2300 DHT (6X2) (1987-1990)



## BOGIE LIFT

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF-A</b>             |

## HYDRAULIC CAB TILT SYSTEM

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF-A</b>             |

## HYDRAULIC CLUTCH SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

## POWER STEERING

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       | <b>ATF-A</b>             |

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

## WHEEL BEARINGS FRONT OIL LUBRICATED

Capacity: 0,5 liter

| USE                         |                             | CLIMATE                            |
|-----------------------------|-----------------------------|------------------------------------|
| Normal                      |                             | Moderate                           |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3           |
| <b>Gearlube GL-4 80W-90</b> | <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |

Change every 12 months

# DAF F2100, F2300, F2500 F2300 DHT (6X2) (1987-1990)



## COOLING SYSTEM

Capacity: 35 liter

### USE

Normal

### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

#### PRODUCT RECOMMENDATION 2

**Coolant SP 12**

#### PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*