## DANA SPICER AXLES AXLES, CONVERTABLE TANDEM S21-060B



apacity: 17,5 liter	Dana S21-060	
JSE		CLIMATE
Standard, line haul		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Change every 200000 km/ 12 months		
JSE		CLIMATE
Standard, line haul		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 200000 km/ 12 months		
USE		CLIMATE
Standard, vocational/bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Change every 100000 km/ 12 months		
USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 100000 km/ 12 months		
USE		CLIMATE
Line haul, extended service, axles	with LMS wheel bearing system	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 800000 km/ 60 months		
USE		CLIMATE
Vocational, extended service, axlessystem	s with adjustable wheel bearing	Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 100000 km/ 12 months		
USE		CLIMATE
Vocational, extended service , axle	s with LMS wheel bearing system	Moderate
	PRODUCT RECOMMENDATION 2	
PRODUCT RECOMMENDATION 1		

## DANA SPICER AXLES AXLES, CONVERTABLE TANDEM S21-060B



USE		CLIMATE
Line haul, extended service, axles with adjustable wheel bearing system		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 400000 km/ 36 months		
USE		CLIMATE
Initial service, standard		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90
Change every 8000 km		
USE		CLIMATE
Initial service, standard		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 8000 km		
USE		CLIMATE
Initial service, extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change every 8000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.