## DANA SPICER AXLES AXLES, TANDEM DRIVE DDH/RDH44



| AXLE TANDEM DRIVE Dana DDH/RDH4<br>Capacity: 13,2 liter (DDH), Capacity: 14,7 |                               |                          |
|---|-------------------------------|--------------------------|
| USE   |                               | CLIMATE                  |
| Standard, line haul   |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140   | SP Gear 1011                  | Syngear TDL 75W-90       |
| Change every 200000 km/ 12 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Standard, line haul   |                               | Arctic                   |
| PRODUCT RECOMMENDATION 1  |                               |                          |
| SP Gear 5015  |                               |                          |
| Change every 200000 km/ 12 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Standard, vocational/bus  |                               | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
| Gearlube Racing 75W-140   | SP Gear 1011                  | Syngear TDL 75W-90       |
| Change every 100000 km/ 12 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Standard, vocational/bus  |                               | Arctic                   |
| PRODUCT RECOMMENDATION 1  |                               |                          |
| SP Gear 5015  |                               |                          |
| Change every 100000 km/ 12 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Line haul, extended service, axles w  | ith LMS wheel bearing system  | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      |                          |
| SP Gear 1011  | Syngear TDL 75W-90            |                          |
| Change every 800000 km/ 60 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Vocational, extended service, axles   | with adjustable wheel bearing | Moderate                 |
| system  |                               |                          |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      |                          |
| SP Gear 1011  | Syngear TDL 75W-90            |                          |
| Change every 100000 km/ 12 months   |                               |                          |
| USE   |                               | CLIMATE                  |
| Vocational, extended service , axles  | with LMS wheel bearing system | Moderate                 |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2      |                          |
| SP Gear 1011  | Syngear TDL 75W-90            |                          |
| Change every 200000 km/ 12 months   |                               |                          |

## DANA SPICER AXLES AXLES, TANDEM DRIVE DDH/RDH44



| USE   |                          | CLIMATE                  |  |
|---|--------------------------|--------------------------|--|
| Line haul, extended service, axles with adjustable wheel bearing system |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |                          |  |
| SP Gear 1011  | Syngear TDL 75W-90       |                          |  |
| Change every 400000 km/ 36 months                                       |                          |                          |  |
| USE   |                          | CLIMATE                  |  |
| Initial service, standard   |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |
| Gearlube Racing 75W-140   | SP Gear 1011             | Syngear TDL 75W-90       |  |
| Change every 8000 km  |                          |                          |  |
| USE   |                          | CLIMATE                  |  |
| Initial service, standard   |                          | Arctic                   |  |
| PRODUCT RECOMMENDATION 1  |                          |                          |  |
| SP Gear 5015  |                          |                          |  |
| Change every 8000 km  |                          |                          |  |
| USE   |                          | CLIMATE                  |  |
| Initial service, extended   |                          | Moderate                 |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |                          |  |
| SP Gear 1011  | Syngear TDL 75W-90       |                          |  |
| Change every 8000 km  |                          |                          |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.