

DANA SPICER AXLES STEERING AXLES, I AND D FAMILY D-800F



KING PIN JOINT

USE		CLIMATE
Line haul		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 40000 km/ 6 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

TIE ROD END

USE		CLIMATE
Line haul		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 40000 km/ 6 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

WHEEL BEARINGS (ADJUSTABLE)

USE		CLIMATE
Line haul, oil bath		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 200000 km/ 12 months

USE		CLIMATE
Line haul, oil bath		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 200000 km/ 12 months

DANA SPICER AXLES STEERING AXLES, I AND D FAMILY D-800F



USE		CLIMATE
Line haul, grease pack		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 200000 km/ 12 months

USE		CLIMATE
Vocational, oil bath		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Change every 100000 km/ 6 months

USE		CLIMATE
Vocational, oil bath		Arctic
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Change every 100000 km/ 6 months

USE		CLIMATE
Vocational, grease pack		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 100000 km/ 6 months

WHEEL BEARINGS (LMS SYSTEM)		
USE		CLIMATE
Line haul		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 800000 km/ 60 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Change every 200000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.