## DANA SPICER AXLES STEERING AXLES, I AND D FAMILY I-160S



KING PIN JOINT			
USE		CLIMATE	
Line haul		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 40000 km/ 6 months			
USE		CLIMATE	
Vocational		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

USE		CLIMATE
Line haul		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 40000 km/ 6 months	5	
JSE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

WHEEL BEARINGS (ADJUSTABLE)			
use Line haul, oil bath		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90	
Change every 200000 km/ 12 months			
USE		CLIMATE	
Line haul, oil bath		Arctic	
PRODUCT RECOMMENDATION 1			
SP Gear 5015			
Change every 200000 km/ 12 months	'		

## DANA SPICER AXLES STEERING AXLES, I AND D FAMILY I-160S



PRODUCT RECOMMENDATION 2	Moderate  PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 2
	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90
	CLIMATE
	Arctic
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
	PRODUCT RECOMMENDATION 2 SP Gear 1011  PRODUCT RECOMMENDATION 2

WHEEL BEARINGS (LMS SYSTEM)			
USE		CLIMATE	
Line haul		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

Change every 800000 km/60 months

USE		CLIMATE
Vocational		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
0/ 0000001 /04	4	

Change every 200000 km/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.