

DETROIT DIESEL SERIES MBE900 MBE 924

(2002 AND AFTER)



ENGINE MBE 924

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
Dieselfleet CD+ 15W-40		

Change every 9600 km

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 9600 km

USE	CLIMATE
Long distance	Moderate

PRODUCT RECOMMENDATION 1		
Dieselfleet CD+ 15W-40		

Change every 24000 km

USE	CLIMATE
Long distance	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 24000 km

USE	CLIMATE
Distribution	Moderate

PRODUCT RECOMMENDATION 1		
Dieselfleet CD+ 15W-40		

Change every 19200 km

USE	CLIMATE
Distribution	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth LSP Ultra 10W-40	Armado Synth LSP 10W-40	Armado Synth 10W-40

Change every 19200 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.