## **EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-12210B**



Multifleet SCD 50 Multifleet SCD 40	Moderate  PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	
Multifleet SCD 50 Multifleet SCD 40	I KODOCI KECOMMENDATION 3
Change every 100000 km	Gearlube GL-4 80W-90
SE	CLIMATE
Standard, line haul	Arctic
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	
Multifleet SCD 30 Gear Oil Alcat 30	
Change every 100000 km	
JSE	CLIMATE
Standard, vocational/bus	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50 Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 100000 km/ 12 months	
JSE	CLIMATE
Standard, vocational/bus	Arctic
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	
Multifleet SCD 30 Gear Oil Alcat 30	
Change every 100000 km/ 12 months	
SE	CLIMATE
Standard, stationary	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50 Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 500 hours/ 12 months	
JSE	CLIMATE
Standard, stationary	Arctic
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	
Multifleet SCD 30 Gear Oil Alcat 30	
Change every 500 hours/ 12 months	
JSE	CLIMATE
Standard, initial service, stationary	Moderate
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3  Gearlube GL-4 80W-90

## EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-12210B



USE		CLIMATE
Standard, initial service, stationary		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 2 months/ 40 hours	·	
USE		CLIMATE
Standard, initial service, on highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 8000 km		
USE		CLIMATE
Standard, initial service, on highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km	•	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.