EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-17210C



Capacity: 11 liter		
sse Standard, line haul		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 100000 km		
ISE		CLIMATE
Standard, line haul		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 100000 km	I	
JSE		CLIMATE
Standard, vocational/bus		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 100000 km/ 12 months		
USE		CLIMATE
Standard, vocational/bus		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 100000 km/ 12 months		
JSE -		CLIMATE
Standard, stationary		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 500 hours/ 12 months		
use Standard, stationary		CLIMATE Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Alctic
Multifleet SCD 30	Gear Oil Alcat 30	
	Godi Gii 7 iidat Go	
Change every 500 hours/ 12 months JSE		CLIMATE
Joe		Moderate
Standard initial service stationary		
Standard, initial service, stationary	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3

EATON FULLER HEAVY-DUTY TRANSMISSIONS 10 SPEED FRO-17210C



USE		CLIMATE
Standard, initial service, stationary		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 2 months/ 40 hours		
USE		CLIMATE
Standard, initial service, on highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gearlube GL-4 80W-90
Change every 8000 km		
USE		CLIMATE
Standard, initial service, on highway	/ use	Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km	,	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.