## EATON FULLER HEAVY-DUTY TRANSMISSIONS 13 -> 18 SPEED RTLOF14913A



<b>FRANSMISSION</b> Eaton-Fuller 1491 Capacity: 13,2 liter		
JSE		CLIMATE
Off Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
Change every 30 hours		
USE		CLIMATE
Off Highway use, initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 30 hours		
USE		CLIMATE
Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
Change every 8000 km		
USE		CLIMATE
Highway use, initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Change every 8000 km		
USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
Check every 40 hours, change ever	y 500 hours	
USE		CLIMATE
Off-Highway use, severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 40 hours, change ever	y 500 hours	
		CLIMATE
USE		Moderate
use Off-Highway use		
	PRODUCT RECOMMENDATION 2  Multifleet SCD 40	PRODUCT RECOMMENDATION 3  Gear Oil Alcat 50

Check every 16000 km, change every 160000 km

## EATON FULLER HEAVY-DUTY TRANSMISSIONS 13 -> 18 SPEED RTLOF14913A



USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 40 hours, change every	1000 hours	
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	Gear Oil Alcat 50
Check every 16000 km, change ever	y 160000 km	
USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.