EATON FULLER HEAVY-DUTY TRANSMISSIONS 13 -> 18 SPEED RTLO9118A-MT



TRANSMISSION Eaton-Fuller 9118 18 Capacity: 26,5 liter		
USE		CLIMATE
Off Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 30 hours		
USE		CLIMATE
Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 2500 km		
USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40 hours, change every 500 hours		
USE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40 hours, change every 1000	hours	
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 4000 km, change every 80000 km/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.