## EATON FULLER MEDIUM-DUTY **TRANSMISSIONS FS-6205B**



use CLIMATE Moderate Highway use, initial service Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Cear Oil Alcat 50 Change every 8000 km Use CLIMATE Arctic PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Change every 8000 km Use CLIMATE CLIMATE Off-Highway use, severe Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT REC	TRANSMISSION Eaton-Fuller 6205 5	/1			
Highway use, initial service         Moderate           PRODUCT RECOMMENDATION 1         PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 3           Gear Oil Alcat 50         Gear Oil Alcat 50           Change every 8000 km         CLIMATE           Viel Highway use, initial service         CLIMATE           PRODUCT RECOMMENDATION 1         PRODUCT RECOMMENDATION 2         Gear Oil Alcat 30           Change every 8000 km         Gear Oil Alcat 30         CLIMATE           Off-Highway use, severe         Moderate         Moderate           PRODUCT RECOMMENDATION 1         PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 3           Multifleet SCD 50         Multifleet SCD 40         Gear Oil Alcat 50           Charge every 40 hours, change every 500 -burs         VEE         CLIMATE           Off-Highway use, severe         FroDUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 3           Multifleet SCD 30         ClimATE         CLIMATE           Off-Highway use, severe         CLIMATE         CLIMATE           Off-Highway use         FroDUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 3           Multifleet SCD 30         Multifleet SCD 40         Gear Oil Alcat 50           Charge every 40 hours, change every 1000-burs         CLIMATE         CLIMATE           Off-Hi	Capacity: 8,99 liter				
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Gear Oil Alcat 50 Change every 8000 km Use CLMATE Highway use, initial service PRODUCT RECOMMENDATION 2 Multifleet SCD 30 Cear Oil Alcat 30 Change every 8000 km Use CLMATE Off-Highway use, severe PRODUCT RECOMMENDATION 2 Multifleet SCD 50 Multifleet SCD 40 Charge every 40 hours, change every 500 hours Use CLMATE Off-Highway use CLMATE Off-Highway use CLMATE CIMATE Off-Highway use CLMATE CLMATE Off-Highway use CLMATE Off-Highway use CLMATE Off-Highwa					
Multifieet SCD 50     Multifieet SCD 40     Gear Oil Alcat 50       Change every 8000 km     CLIMATE       Highway use, initial service     PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2       Multifieet SCD 30     Gar Oil Alcat 30     Image every 8000 km       Change every 8000 km     Gar Oil Alcat 30     Image every 8000 km       Use     CLIMATE     Moderate       Off-Highway use, severe     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifieet SCD 50     Multifieet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 500 Juris     CLIMATE     Off-Highway use, severe       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifieet SCD 30     ClimATE     Off-Highway use, severe       Off-Highway use, severe     CLIMATE     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 2       Multifieet SCD 30     Multifieet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 100 Juris     PRODUCT RECOMMENDATION 3       Multifieet SCD 50     Multifieet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 100 Juris     Gear Oil Alcat 30     Gear Oil Alcat 50       Check every 40 hours, change every 100 Juris     CLIMATE     Gear Oil Alcat 30       Check every 4					
Change every 8000 km       CLMATE         Highway use, initial service       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Change every 8000 km       Use         Off-Highway use, severe       CLMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 50       Multifleet SCD 40         Gear Oil Alcat 50       Gear Oil Alcat 50         Check every 40 hours, change every 500 hours       Use         Off-Highway use, severe       CLMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 500 hours       Use         Off-Highway use, severe       CLMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       Use         Use       CLMATE         Off-Highway use       PRODUCT RECOMMENDATION 2         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       Gear Oil Alcat 30         Use       CLMATE       G					
USE CLIMATE Highway use, initial service Arctic PRODUCT RECOMMENDATION 1 Multifileet SCD 30 Change every 8000 km USE CLIMATE Off-Highway use, severe Moderate PRODUCT RECOMMENDATION 1 Multifileet SCD 50 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use, severe Arctic PRODUCT RECOMMENDATION 1 Multifileet SCD 50 Climate CLIMATE Off-Highway use, severe CLIMATE CLIMATE Off-Highway use, severe CLIMATE CLIMATE Off-Highway use, severe CLIMATE CLIMATE Off-Highway use, severe CLIMATE Off-Highway use, severe CLIMATE Off-Highway use, severe CLIMATE Off-Highway use SCD 30 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use Moderate PRODUCT RECOMMENDATION 1 Multifieet SCD 30 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use CLIMATE PRODUCT RECOMMENDATION 1 Multifieet SCD 50 Check every 40 hours, change every 1000 hours USE CLIMATE Off-Highway use CLIMATE PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE PRODUCT RECOMMENDATION 1					
Highway use, initial service       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 30         Change every 8000 km       E       ELMATE         USE       CLMATE       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 50         Multified SCD 50       Multified SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 500 hours       E       CLMATE         VIE       CLMATE       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 50         Check every 40 hours, change every 500 hours       E       CLMATE         VIE       CLMATE       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 30         Check every 40 hours, change every 500 hours       E       E         USE       CLIMATE       Multified SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       E       Multified SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       E       E       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       E       Gear Oil Alcat 50         Check every 40 hours, change					
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Change every 8000 km USE CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 1 Multifleet SCD 50 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 Multifleet SCD 40 CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 PRODUCT RECOMMENDATION 3 PRODUCT					
Multifleet SCD 30     Gear Oil Alcat 30       Climate       Climate       OIL Alcat 30       OIL Alcat 30       OIL Alcat 30       OIL Alcat 30       OIL Alcat 50       PRODUCT RECOMMENDATION 1       Multifleet SCD 50     Multifleet SCD 40       Gear Oil Alcat 50       Climate       Climate       OIL Alcat 50       Climate       Climate       OIL Alcat 50       Climate       OIL Alcat 30       OIL Alcat 30       Climate       OIL Alcat 30       OIL Alcat 30			Alctic		
Change every 8000 km       CLIMATE         VSE       CLIMATE         Off-Highway use, severe       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 500 hours       USE       CLIMATE         Off-Highway use, severe       Arctic       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 30         Check every 40 hours, change every 500 hours       Gear Oil Alcat 30       CLIMATE         Off-Highway use       PRODUCT RECOMMENDATION 2       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       VSE       CLIMATE         VSE       CLIMATE       CLIMATE         Off-Highway use       Arctic       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Gear Oil Alcat 50         Multifleet SCD 30       CLIMATE       CLIMATE       CLIMATE         Off-Highway use       Arctic       Gear Oil Alcat 30       CLIMATE </td <td></td> <td></td> <td></td>					
CLIMATE       Off-Highway use, severe     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 500 hours     USE     CLIMATE       Off-Highway use, severe     Arctic     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     CLIMATE       Multifleet SCD 30     Car Oil Alcat 30     Climate       Check every 40 hours, change every 500 hours     USE     CLIMATE       Off-Highway use     FooDuct RECOMMENDATION 2     Climate       Multifleet SCD 30     Climate     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 1000 hours     USE     CLIMATE       Off-Highway use     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 30     Gear Oil Alcat 30       Check every 40 hours, change every 1000 hours     Gear Oil Alcat 30       USE     CLIMATE     Gear Oil Alcat 30       Check every 40 hours, change every 1000 hours     Gear Oil Alcat 30       Check every 40 hours, change every 1000 hours     Gear Oil Alcat 30		Geal Oll Alcal 30			
Of-Highway use, severe     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 500 hours     Sear Oil Alcat 50       CLIMATE       Off-Highway use, severe     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     Multifleet SCD 30       CLIMATE       Off-Highway use     CLIMATE       Multifleet SCD 50     Noutr RECOMMENDATION 2     PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 1000- hours     Use     CLIMATE       Off-Highway use     CLIMATE     Gear Oil Alcat 50       Check every 40 hours, change every 1000- hours     CLIMATE     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     Gear Oil Alcat 30       Check every 40 hours, change every 1000- hours     Gear Oil Alcat 30     Climate       Off-Highway use     Gear Oil Alcat 30     Climate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     Moderate       PRODUCT R					
PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Multifleet SCD 50 Multifleet SCD 40 Gear Oil Alcat 50 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATI					
Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 500 burs     CLIMATE       Off-Highway use, severe     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     Arctic       Multifleet SCD 30     Gear Oil Alcat 30     CLIMATE       Check every 40 hours, change every 500 burs     Gear Oil Alcat 30     Moderate       Vise     CLIMATE     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 1000-     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 1000-     Multifleet SCD 40     Gear Oil Alcat 50       Check every 40 hours, change every 1000-     Gear Oil Alcat 30     ClimATE       Off-Highway use     PRODUCT RECOMMENDATION 2     CLIMATE       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     CLIMATE       Multifleet SCD 30     Gear Oil Alcat 30     ClimATE       Check every 40 hours, change every 1000-     Gear Oil Alcat 30     PRODUCT RECOMMENDATION 2       Check every 40 hours, change every 1000-     Gear Oil Alcat 30     PRODUCT RECOMMENDATION 2       Check every 40 hours, change every 1000-     Gear Oil Alcat 30     PRODUCT RECOMMENDATION 2 <td< td=""><td></td><td></td><td></td></td<>					
Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use, severe PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Multifleet SCD 50 Multifleet SCD 40 Check every 40 hours, change every 1000 hours USE CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 CLIMATE Off-Highway use CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 CLIMATE Highway use PRODUCT RECOMMENDATION 2 PR					
USE CLIMATE Arctic PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30 Check every 40 hours, change every 500 hours USE CLIMATE Off-Highway use Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Multifleet SCD 50 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 2 Check every 40 hours, change every 1000 hours USE CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 Check every 40 hours, change every 1000 hours USE CLIMATE Nultifleet SCD 30 Check every 40 hours, change every 1000 hours USE CLIMATE Off-Highway use PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 P			Geal Of Alcal 30		
Off-Highway use, severe     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2 Gear Oil Alcat 30     Image: Comparison of the co		600 hours			
PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Gear Oil Alcat 30       Gear Oil Alcat 30         Check every 40 hours, change every 500 hours       USE         Off-Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         USE       CLIMATE         Off-Highway use       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         USE       CLIMATE         Off-Highway use       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       USE         USE       CLIMATE         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       USE         USE       CLIMATE         Multifleet SCD 30       Highway use         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1					
Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 500 +ours         USE       CLIMATE         Off-Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 +ours       USE       CLIMATE         Off-Highway use       CLIMATE       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Multifleet SCD 30         Check every 40 hours, change every 1000 +ours       Gear Oil Alcat 30       CliMATE         Multifleet SCD 30       PRODUCT RECOMMENDATION 2       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Gear Oil Alcat 50       Multifleet SCD 40       PRODUCT RECOMMENDATION 3			Alcuc		
Check every 40 hours, change every 500 hours         USE       CLIMATE         Off-Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       USE       CLIMATE         Off-Highway use       CLIMATE       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         Off-Highway use       Gear Oil Alcat 30       CLIMATE         Multifleet SCD 30       Gear Oil Alcat 30       CLIMATE         USE       CLIMATE       Moderate         Highway use       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         USE       CLIMATE       Moderate       PRODUCT RECOMMENDATION 3         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50					
USE       CLIMATE         Off-Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       Image: Climate       Climate         USE       CLIMATE       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       Climate         Multifleet SCD 30       Gear Oil Alcat 30       Climate         Check every 40 hours, change every 1000 hours       Gear Oil Alcat 30       Climate         VSE       Climate       Multifleet SCD 30       For Oil Alcat 30         Check every 40 hours, change every 1000 hours       For Oil Alcat 30       For Oil Alcat 30         Check every 40 hours, change every 1000 hours       For Oil Alcat 30       For Oil Alcat 30         Check every 40 hours, change every 1000 hours       For Oil Alcat 30       For Oil Alcat 30         Check every 40 hours, change every 1000 hours       For Oil Alcat 30       For Oil Alcat 30         Gear Oil Alcat 50       Multifleet SCD 40       For Oil Alcat 50					
Off-Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 +ours       ELIMATE         Off-Highway use       CLIMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 +ours       ELIMATE         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 +ours       ELIMATE         Multifleet SCD 30       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       Multifleet SCD 40					
PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50         Check every 40 hours, change every 1000 hours       CLIMATE         Off-Highway use       CLIMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Gear Oil Alcat 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       CLIMATE         Multifleet SCD 30       Rear Oil Alcat 30         Check every 40 hours, change every 1000 hours       Multifleet SCD 50					
Multifleet SCD 50Multifleet SCD 40Gear Oil Alcat 50Check every 40 hours, change every 1000 hoursUSECLIMATEOff-Highway usePRODUCT RECOMMENDATION 2ArcticPRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 2Gear Oil Alcat 30Multifleet SCD 30Gear Oil Alcat 30ClimateCheck every 40 hours, change every 1000 hoursUSECLIMATEHighway usePRODUCT RECOMMENDATION 2ModeratePRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 3Multifleet SCD 50Multifleet SCD 40Gear Oil Alcat 50					
Check every 40 hours, change every 1000 hours         USE       CLIMATE         Off-Highway use       Arctic         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours       CLIMATE         USE       CLIMATE         Highway use       CLIMATE         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         USE       CLIMATE         Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50					
USE     CLIMATE       Off-Highway use     Arctic       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2       Multifleet SCD 30     Gear Oil Alcat 30       Check every 40 hours, change every 1000 hours     CLIMATE       USE     CLIMATE       Highway use     CLIMATE       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2       Multifleet SCD 50     Multifleet SCD 40					
Off-Highway useArcticPRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 2Multifleet SCD 30Gear Oil Alcat 30Check every 40 hours, change every 1000 hoursCLIMATEModerateHighway usePRODUCT RECOMMENDATION 1PRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 2PRODUCT RECOMMENDATION 1Multifleet SCD 40PRODUCT RECOMMENDATION 3Gear Oil Alcat 50		1000 nours			
PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours         USE       CLIMATE         Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2         Multifleet SCD 50       Multifleet SCD 40					
Multifleet SCD 30       Gear Oil Alcat 30         Check every 40 hours, change every 1000 hours         use       CLIMATE         Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50		PRODUCT RECOMMENDATION 2			
Check every 40 hours, change every 1000 hours         USE       CLIMATE         Highway use       Moderate         PRODUCT RECOMMENDATION 1       PRODUCT RECOMMENDATION 2       PRODUCT RECOMMENDATION 3         Multifleet SCD 50       Multifleet SCD 40       Gear Oil Alcat 50					
USE     CLIMATE       Highway use     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50					
Highway use     Moderate       PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50					
PRODUCT RECOMMENDATION 1     PRODUCT RECOMMENDATION 2     PRODUCT RECOMMENDATION 3       Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50					
Multifleet SCD 50     Multifleet SCD 40     Gear Oil Alcat 50		PRODUCT RECOMMENDATION 2			
	Check every 16000 km, change every				

## EATON FULLER MEDIUM-DUTY TRANSMISSIONS FS-6205B



USE		CLIMATE		
Highway use		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Multifleet SCD 30	Gear Oil Alcat 30			
Check every 16000 km, change every 80000 km				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.