EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-11605A



		CLIMATE
se Off Highway use, initial service		climate Mediterranean
PRODUCT RECOMMENDATION 1		Mediterranean
Gearlube GL-4 80W-90		
Change every 30 hours		
USE		CLIMATE
Off Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50
Change every 30 hours		
USE		CLIMATE
Off Highway use, initial service		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	HDX 30	
Change every 30 hours		
USE		CLIMATE
Highway use, initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
Change every 8000 km		
USE		CLIMATE
Highway use, initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50
Change every 8000 km		
USE		CLIMATE
Highway use, initial service	_	Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	HDX 30	
Change every 8000 km		
USE		CLIMATE
Off-Highway use, severe		Mediterranean
- 9 -,		

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-11605A



USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1 Multifleet SCD 50	PRODUCT RECOMMENDATION 2 Multifleet SCD 40	PRODUCT RECOMMENDATION 3 HDX 50
		HDX 90
Check every 40 hours, change every	v 500 hours	
Off-Highway use, severe		CLIMATE Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	Aictic
Multifleet SCD 30	HDX 30	
Check every 40 hours, change every	500 hours	,
USE		CLIMATE
Off-Highway use		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
Check every 40 hours, change every	1000 hours	
USE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50
Check every 40 hours, change every	1000 hours	
USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	HDX 30	
Check every 40 hours, change every	v 1000 hours	
USE Llighway yan		CLIMATE
Highway use		Mediterranean
PRODUCT RECOMMENDATION 1 Gearlube GL-4 80W-90		
Check every 16000 km, change ever	y 80000 km	
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 50	Multifleet SCD 40	HDX 50

PRODUCT RECOMMENDATION

EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED T-11605A



use Highway use		climate Arctic		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 30	HDX 30			
Check every 16000 km, change every 80000 km				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.