

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED TO-11605C



**TRANSMISSION** Eaton-Fuller 11605 5/1  
Capacity: 10 liter

USE	CLIMATE
Off Highway use, initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

*Change every 30 hours*

USE	CLIMATE
Off Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 50**

PRODUCT RECOMMENDATION 2

**Multifleet SCD 40**

PRODUCT RECOMMENDATION 3

**HDX 50**

*Change every 30 hours*

USE	CLIMATE
Off Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

PRODUCT RECOMMENDATION 2

**HDX 30**

*Change every 30 hours*

USE	CLIMATE
Highway use, initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

*Change every 8000 km*

USE	CLIMATE
Highway use, initial service	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 50**

PRODUCT RECOMMENDATION 2

**Multifleet SCD 40**

PRODUCT RECOMMENDATION 3

**HDX 50**

*Change every 8000 km*

USE	CLIMATE
Highway use, initial service	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30**

PRODUCT RECOMMENDATION 2

**HDX 30**

*Change every 8000 km*

USE	CLIMATE
Off-Highway use, severe	Mediterranean

PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

*Check every 40 hours, change every 500 hours*

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED TO-11605C



USE		CLIMATE
Off-Highway use, severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>
<i>Check every 40 hours, change every 500 hours</i>		
USE		CLIMATE
Off-Highway use, severe		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>HDX 30</b>	
<i>Check every 40 hours, change every 500 hours</i>		
USE		CLIMATE
Off-Highway use		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-4 80W-90</b>		
<i>Check every 40 hours, change every 1000 hours</i>		
USE		CLIMATE
Off-Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>
<i>Check every 40 hours, change every 1000 hours</i>		
USE		CLIMATE
Off-Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>HDX 30</b>	
<i>Check every 40 hours, change every 1000 hours</i>		
USE		CLIMATE
Highway use		Mediterranean
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-4 80W-90</b>		
<i>Check every 16000 km, change every 80000 km</i>		
USE		CLIMATE
Highway use		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	<b>HDX 50</b>
<i>Check every 16000 km, change every 80000 km</i>		

# EATON FULLER HEAVY-DUTY TRANSMISSIONS 5 -> 7 SPEED TO-11605C



USE		CLIMATE
Highway use		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 30</b>	<b>HDX 30</b>	
Check every 16000 km, change every 80000 km		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*